



Piezo Buzzer Series

RE-B-PB- 43*28C With Circuit Piezo Buzzer Series

SPECIFICATION

Rated Voltage: 12V_{DC}
 Operating Voltage: 6-28V_{DC}
 Max. Rated Current: 20mA at 12V_{DC}
 Min. S.P.L. (@60cm): 80dB at 12V_{DC}
 Resonant Frequency: 2.9 ± 0.5KHz
 Tone Nature: Continuous
 Operating Temp: -20~+80°C
 Weight: 36g

Order Code	Rated Voltage	Operating Voltage	Max. Rated Current	Min. S.P.L. (@60cm)	Resonant Frequency	Tone Nature	Operating Temp	Weight
RE-B-PB-43*28C-A1	12V _{DC}	6-28V _{DC}	20mA	80dB	2.9 ± 0.5KHz	Continuous	-20~+80°C	36g
RE-B-PB-43*28C-A2	12V _{DC}	6-28V _{DC}	20mA	80dB	2.9 ± 0.5KHz	Slow Pulse		
RE-B-PB-43*28C-A3	12V _{DC}	6-28V _{DC}	20mA	80dB	2.9 ± 0.5KHz	Fast Pulse		
RE-B-PB-43*28C-A4	12V _{DC}	6-28V _{DC}	20mA	80dB	2.9 ± 0.5KHz	Continuous + Slow Pulse		
RE-B-PB-43*28C-A5	12V _{DC}	6-28V _{DC}	20mA	80dB	2.9 ± 0.5KHz	Continuous + Fast Pulse		
RE-B-PB-43*28C-B1	230V _{AC}	200~ 240V _{AC}		80dB	2.9 ± 0.5KHz	Continuous		
RE-B-PB-43*28C-B2	230V _{AC}	200~ 240V _{AC}		80dB	2.9 ± 0.5KHz	Fast Pulse		
RE-B-PB-43*28C-B3	230V _{AC}	200~ 240V _{AC}		80dB	2.9 ± 0.5KHz	Slow Pulse		

ORDER INFORMATION

Product NO.: RE-B- PB - 43*28C -A1

Part Number

Piezo Buzzer Series

Order Code