



PHOTO ONLY FOR REFERENCE

NOTE:

1.MATERIAL:

- a.HOUSING: PA66 V-0
- b.CONTACT: PHOSPHOR BRONZE
(SURFACE PLATING: Ni 100U"~120U)

2.ELECTRIC:

- a.CONTACT RESISTANCE: 100 MILLIOHMS MAX
- b.INSULATION RESISTANCE: 100 MEGA OHMS MIN
- c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
- d.OPERATING TEMPERATURE: -25°C~ +85°C

PCB Layout Diagram
Top View

DECIMALS: X :±0.30 X.X :±0.25 X.XX :±0.20 X.XXX:±0.10	ANGLES: :±1° X.X:±0.5°	DSND	DATE	2020-04-02	TITLE:	RE-BH-CR2032-01
WEIGHT:1.56g		CHKD	DATE		PART NO.:	RE-BH-CR2032-01
SHEET 1 OF 1		APVD	DATE	2020-04-02	DRAW NO.:	
UNIT:mm		SCALE:2:1	SIZE:A4	VIEW:		

③	TERMINAL(-)	1	PHOSPHOR BRONZE,T=0.2mm	Ni Plating
②	TERMINAL(+)	1	PHOSPHOR BRONZE,T=0.4mm	Ni Plating
①	HOUSING	1	PA66 V-0	BLACK
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR