



Product Description:

UL STYLE: UL2651
 Rate temperature : 105°C
 Rate voltage : 300V
 Flame test : VW-1 & CSA FT1,FT2
 Conductor: 26~30AWG , Tinned Copper
 Insulation : PVC, Color: Gray

ELECTRONIC CHARACTERISTICS:

Spark test : 2500V
 Dielectric strength test : 2KV in 1 minute Min.
 Insulation resistance : 127MΩ/km Min.

Order Information:

RE - CAb - 127 - FC - XX - X / XX

Pitch: 1.27mm

FC: Flat Ribbon Cable

Pin Number: 04P 08P 10P 12P 14P
 16P 20P 24P 26P 30P
 34P 40P 50P 60P 64P

Standard PUT-UP:

1- 30.5M/Roll 3- 153M/Roll (<40P)
 2- 76.5M/Roll 4- 305M/Roll (<8P)

Conductor AWG:

None - 30AWG(7/0.10TS)
 28 - 28AWG(7/0.12TS)
 26 - 26AWG(7/0.16TS)

Conductor				Insulation		Conductor resistance Max. at 20°C, DC
AWG	Construction	DIA.	Pin Number	Thickness	OD	
	mm	mm		mm	mm	Ω/km
30	7/0.10	0.30	4~64	0.26	0.85	376.96
28	7/0.12	0.39	4~64	0.26	0.90	237.25
26	7/0.16	0.49	4~64	0.26	1.00	148.94