



**Note:**

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

**Order Information**  
**RE-ANT-RFCA01-RG174-L300**

Lengs: L300=300mm  
 Cable: RG174 Cable or RG316 Cable  
 Series: SMA Female-MMCX Male R/A  
 RoHS

No.	Name	Description	UNITS	Q'ty
6	Nut	T1.8mm Nut, 1/4 36UNS-2A	PCS	1
5	Washers	T0.4mm Washers	PCS	1
4	Connector	SMA Jack, Female Straight, for RG174, with CAP(Red)	PCS	1
3	RF Cable	RG174 Cable, Black, OD2.7mm	mm	L
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Block, L 15mm	PCS	2
1	Connector	MMCX Plug Right angle, for RG174 or RG316	PCS	1

UNITS:mm		SHEET SIZE:A4		SCALE: ---		First angle projection
> 0 ~ 3	> 3 ~ 18	> 18 ~ 50	> 50 ~ 120			
± 0.12	± 0.15	± 0.3	± 0.5	Antenna		