



Note:

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information
RE - ANT - RFCA29 - RG174 - L300

Lengs: L300=300mm
 Cable: RG174 Cable or RG316 Cable
 Series: MCX plug, Male Straight to SMA Female
 RoHS

6	Nut	T1.8mm Nut, 1/4 36UNS-2A	PCS	1
5	Washers	T0.4mm Washers	PCS	1
4	Connector	SMA Jack, Female Straight, for RG174, with CAP(Red)	PCS	1
3	RF Cable	RG174 Cable, Black, OD2.7mm	mm	L
2	Heat-Shrink Tube	∅2.5mm Heat-Shrink Tube, Black, L15mm	PCS	2
1	Connector	MCX Plug, Male Straight, for RG174 or RG316	PCS	1
No.	Name	Description	UNITS	Q'ty

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE:A4

SCALE: ---

First angle projection

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

Antenna