



Specifications	
Circuit	:SPDT
Current rating	:12mA
Voltage rating	:24VDC
Dielectric withstanding voltage	:250VAC for 1 minute
Contact resistance	:50mΩ Max. (Initial)
Insulation resistance	:100MΩ Min.
Operating force	:170±50gf
Total travel	:2.0mm±0.4mm
Mechanical life	:Over 50,000 cycles
Electrical life	:Over 10,000 cycles
Solder specifications	:256±5°C for 5 ±0.5 seconds
Function	:Momentary
Operating temperature	:-20° C ~ +70° C

MATERIAL

Base:PBT, UL rated: 94V-2 Min.;
 Cap: ABS;
 Terminal: Phosphor bronze, Golden plated.



P.C.B . Layout



Circuit Diagram

O	Orange	橘色
F	Carnation Pink	粉红
C	Carmin	洋红
P	Pansy	紫罗兰
Y	Yellow	黄色
W	White	白色
U	Blue	蓝色
R	Red	红色
G	Green	绿色
B	Black	黑色
A	Gray	灰色
CAP COLOR (Y)		



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:MM	SHEET SIZE:A4	SCALE:---	
>0~3	>3~18	>18~50	>50~120
±0.12	±0.15	±0.3	±0.5

RE-S-MP86-A0-B

SWITCH